

OPTIONS

Flush Volume

- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)

Finish

- Brushed Stainless (SF)
- Polished Chrome (CP)

Power Type

- Battery

Activation

- Sensor

Valve

- Piston

Water Efficiency

- High Efficiency
- Low Consumption

Fixture Type

- Water Closet

Fixture Connection

- Top Spud

Installation

- Concealed

Override

- Electrical (OR)

Compliances & Certifications

- ADA Compliant
- EPD
- BREEAM Water Credit
- Green Globes Water Credit
- cUPC Certified (Requires use of listed vacuum breaker that complies with ASSE 1001)

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard TRF 8156 shown

DESCRIPTION

TruFlush Concealed Sensor Water Closet Flushometer

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Battery powered infrared sensor provides hands free activation
- Vandal-resistant wall plate with electronic override button
- Replaceable piston assembly accessible though front wall plate
- Concealed shut off sleeve adjusts flow rate
- **Not available in USA or Canada**
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

DOWNLOADS

- [TruFlush Sensor Installation Instructions](#)
- [TruFlush Sensor Installation Instructions \(Spanish\)](#)
- [TruFlush Sensor Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ TruFlush
- ▶ TruFlush Installation
- ▶ TruFlush Maintenance
- ▶ TruFlush Flush Line