

OPTIONS**Flush Volume**

- 0.25 gpf (0.9 Lpf) (0.25)
- 0.5 gpf (1.9 Lpf) (0.5)
- 0.125 gpf (0.5 Lpf) (0.125)

Finish

- Polished Chrome (CP)
- Brushed Stainless (SF)

Power Type

- Battery

Activation

- Sensor

Valve

- Piston

Water Efficiency

- High Efficiency

Fixture Type

- Urinal

Fixture Connection

- Top Spud
- Top or Rear Spud (not provided)

Installation

- Concealed

Override

- Electrical (OR)

Compliances & Certifications

- ADA Compliant
- BREEAM Water Credit
- EPD
- Green Globes Water Credit

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard TRF 8196 shown

DESCRIPTION

TruFlush Concealed Sensor Urinal Flushometer

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Battery powered infrared sensor provides hands free activation
- Vandal-resistant wall plate with electronic override button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate
- **Not available in USA or Canada**
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

DOWNLOADS

- [TruFlush Sensor Installation Instructions](#)
- [TruFlush Sensor Installation Instructions \(Spanish\)](#)
- [TruFlush Sensor Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

- ▶ [TruFlush](#)
- ▶ [TruFlush Installation](#)
- ▶ [TruFlush Maintenance](#)
- ▶ [TruFlush Flush Line](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com